

# Index

---

- ABS, 38
- ADPCM, 40, 48
- A-law, 16, 17
- aliasing, 12, 13
- AMR, 71
- AMR-WB, 71, 73
- analog to digital conversion, 10
- anti-aliasing filter, 14
- auditory perception, 37
  
- behavior aggregate, 133
- Bernoulli distribution
  - model, 216
  - traffic assumptions, 215
- bundling, 103
  
- CableLabs, 154
- call management server, 155
- call seizures
  - call server model, 214
  - Poisson source, 212
- CBT, 248
- CGMP, 254
- class based queuing, 120
- class selector codepoint, 133
  
- CMS, 155
- CMTS gate, 154, 155
- codec
  - AAC, 38
  - AC3, 37
  - activity bitrate, 184
  - ADPCM, 40, 48
  - analysis by synthesis, 38, 56
  - bit error rate sensitivity, 50
  - CELP, 61
  - Dolby-Digital, 37
  - embedded, 51
  - G.722, 52
  - G.722.1, 55
  - G.723.1, 66
  - G.726, 40
  - G.727, 51
  - G.728, 69
  - G.729, 64
  - GSM 06.10, 58
  - GSM 06.90, 72
  - GSM FR, 58
  - LPC 10, 36
  - MELP, 36, 37
  - MPEG-2 AAC, 37

- codec (*continued*)
  - network overhead, 185
  - NICAM, 39
  - quality, 74
  - REL P, 57
  - wide-band, 52, 71
- codepoint DiffServ, 133
- coder waveform, 47
- coding
  - entropy, 47
  - Huffman, 47
  - perceptual, 37
- companding, 17
- compressed RTP, 175
- conferences
  - audio multicast, 208
  - audio multi-unicast, 207
  - video, 211
- continuous-time, 11
- controlled load service, 140
- COPS
  - commands, 163
  - profile for DQoS, 161
  - protocol, 160
- critical band analysis, 37
- CRTP, 104, 175, 176
- 
- 
- data stream, 118
- DCME, 48
- DCS, 155
- DECT, 48
- delay versus echo, 90, 107
- Dense mode multicast, 241
- DiffServ, 3
  - as core of RSVP network, 150
  - DS byte, 133
  - DS codepoint, 133
  - IP precedence, 131
  - issues, 135
  - per hop behavior, 133
- dimensioning
  - audio multipoint communications, 206
  - average waiting time, 224
  - call arrivals, 212
  - converged voice-data network, 203
  - large networks and full availability, 220
  - large networks with Erlang B, 221
  - loss rate, 190
  - multiple coders, 198
  - multiple streams, 188, 198
  - overhead, 192
  - queue with finite number of servers, 222
  - single coder, 188
  - single stream, 184
  - small network with Erlang C, 222
  - time probability of waiting, 223
  - traffic matrix, 200
  - video multipoint communications, 211
  - with fault-tolerant network, 202
- discrete time, 11
- discrete-to-continuous conversion, 11
- DOCSIS, 155
- DQoS, 154
  - commands, 163
  - gate, 157
  - sample call flow, 168
  - session, 155
- duplexer, 93
- DVMRP routing table, 241, 243
- 
- 
- echo
  - acoustic, 94
  - canceller, 96
  - electric, 93
  - hybrid, 91, 93
  - listener, 91
  - suppressor, 96
  - talker, 91
  - versus delay, 107
- embedded MTA, 155, 159
- E-model, 113
- EMTA, 155, 159
- Engset distribution

- model, 217
- traffic assumptions, 215
- Erlang first law *see* Erlang B
- Erlang B distribution
  - model, 221
  - traffic assumptions, 215
- Erlang C distribution
  - model, 222
  - traffic assumptions, 215
- exponential distribution, 213
- fair queuing, 120
- fair queuing bitwise round robin, 121
- FIFO queue, 120
- Filter
  - bandpass, 30
  - bank, 37
  - digital, 21
  - high pass, 30
  - long term predictor, 45
  - low pass, 30
  - LPC analysis, 32
  - LPC synthesis, 32
  - LTP, 45
  - notch, 30
  - perceptual weighting, 61
- filters
  - finite impulse response, 25
  - infinite impulse response, 25
- FIR, 26
- formants, 33
- frame
  - per IP packet, 103
  - size, 39, 103
- frequency aliasing, 13
- G.107, 113
- G.131, 107
- G.165, 94, 96
- G.168, 96
- G.711, 16
- G.722, 52
- G.722.1, 55
- G.722.2, 73
- G.723.1 discontinuous transmission,
  - 66, 68
  - G.726, 40, 42, 47
  - G.727, 51
  - G.728, 69
  - G.729, 64
  - GARP, 254
  - gate controller, 155
  - gate DQoS states, 157
  - generalized processor sharing,
    - 122
  - GPS, 122
  - GSM
    - 06.10, 58
    - 06.60, 61
    - 06.90, 72
    - EFR, 71
    - FR, 71
    - Full Rate, 58
    - HR, 71
  - guaranteed service, 140
  - Huffman, 47
  - IGMP
    - snooping, 253
    - v1, 233
    - v2, 235
    - v3, 235
  - IIR, 26
  - impulse response, 25
    - finite, 26
    - infinite, 26
  - integrated services, 140
  - interactivity, 111
  - interleaving, 105
  - IntServ, 4, 140
  - IP precedence filed, 130
  - jitter, 90, 120
  - LD-CELP, 69
  - leaky bucket regulator, 119
  - linear prediction, 30
  - linear prediction coefficients, 44
  - look-ahead, 103
  - LPC analysis, 44

- masking frequency, 37
- mBone, 249
  - SDR, 251
  - VAT, 253
  - VIC, 253
- mean opinion score
  - CMOS, 80
  - common coders, 50
  - DMOS, 80
  - G.722, 54
- modulation pulse amplitude, 10
- MOSPF inter-area routing, 244
- MPEG 2 AAC, 37, 38
- MTA, 154
- multicast, 5, 227
  - address, 230
  - CGMP, 254
  - dense mode, 241
  - DVMRP, 241
  - group, 231
  - IGMPv1, 233
  - IGMPv2, 235
  - IGMPv3, 235
  - mbone, 249
  - MOSPF, 244
  - PIM, 247
  - pruning, 240, 243
  - reverse path broadcasting, 240
  - reverse path multicasting, 240
  - shared tree, 238
  - source based tree, 239
  - spanning tree, 238
  - sparse mode, 241
  - truncated reverse path
    - broadcasting, 240
  - TTL, 236
- multilink-PPP, 177
- multimedia terminal adapter, 154
- NCS, 155
- Nyquist rate, 13
- Nyquist theorem, 13
- overhead compression, 174, 175
- packet by packet generalized
  - processor sharing, 124
- packet fragmentation, 177
- packet loss, 90
- PacketCable, 154
- PAM, 11
- PCM, 14, 49
- PDP, 156
- PEP, 156
- per hop behavior, 133
- perceptual coding, 37
- PGPS, 124
  - delay bound, 126
  - network, 129
  - packet ordering, 128
- PHB, 133
- PIM, 247
  - DM, 247
  - SM, 247
- Poisson distribution traffic
  - assumptions, 215
- Poisson process, 212
- policy decision point, 156
- policy enforcement point, 156
- post-filter, 38
- prediction
  - linear, 44
  - long term, 45
  - temporal, 44
- pulse amplitude modulation, 11
- pulse code modulation, 14, 49
- quantization, 10, 14
- quantizer
  - adaptive, 39
  - backward, 40
  - differential, 42
  - forward, 39
  - linear, 15
  - nonlinear, 16
  - optimal, 17
  - predictive, 42
- random early detection, 120, 173
- RED, 120, 173

- redundancy media transmission, 105
- resource allocation protocol, 156
- reverse path broadcasting, 240
- reverse path forwarding, 241
- reverse path multicasting, 240
- RFC 791, 130
- RFC 1349, 131
- RFC 1990, 177
- RFC 2474, 133
- RFC 2475, 134
- RFC 2686, 178
- RFC 2753, 156
- RSVP, 139
  - controlled load service, 140
  - guaranteed service, 140
  - PATH message, 141
  - RESV message, 142
  - scaling, 145, 148
  - soft states, 145
  - tunneling over DiffServ, 150
- RSVP+, 155, 158
- RTP compressed, 175
- sampling, 10
- sampling Theorem, 12
- scheduling
  - class-based, 120
  - FIFO, 120
  - fair queuing, 120
  - weighted fair queuing, 120
  - policy, 120
- session, 119
- signal residual, 44
- signal processing, 9
- signal-to-noise ration, 15
- SNR, 15
- sound
  - plosive, 33
  - unvoiced, 33
  - voiced, 33
- sparse mode multicast, 241
- speech production, 32
- system
  - causal, 26
  - physically realizable, 26
- TCP slow start, 171
- token bucket regulator, 119
- TOS octet, 130
- traffic-class octet, 130
- traffic matrix, 200
- transfer function, 25
- Truncated Reverse Path Broadcasting, 240
- TTL multicast, 236
- Type of Service, 130
- $\mu$ -law, 16, 17
- UMTS, 72, 73
- VAD Intro, 4, 113
- vocoder, 36
- voice activity rate, 185
- voice activity detection, 4, 113
- voice quality
  - ACR test, 77
  - average level, 112
  - CCR, 80
  - clipping, 112
  - CMOS, 80
  - DCR, 80
  - DMOS, 80
  - E-model, 113
  - interactivity, 111
  - MOS, 77
  - objective measurement, 75
  - subjective measurement, 75
- vocoder LPC 10, 36
- waveform coder, 47
- weighted fair queuing, 120
- weighted random early detection, 120, 173
- WRED, 120, 173
- Z transform
  - table, 23
  - unilateral, 22